US006147996A

United States Patent [19]

Laor et al.

[11] Patent Number: 6,147,996

[45] Date of Patent: Nov. 14, 2000

[54] **PIPELINED MULTIPLE ISSUE PACKET SWITCH**

[75] Inventors: **Michael Laor**, Sunnyvale; **Martin Cieslak**, Fremont, both of Calif.

[73] Assignee: **Cisco Technology, Inc.**, San Jose, Calif.

[21] Appl. No.: **08/511,146**

[22] Filed: **Aug. 4, 1995**

[51] **Int. Cl.**[7] **H04J 12/56**

[52] **U.S. Cl.** **370/394**; 370/412

[58] **Field of Search** 370/389, 392, 370/394, 401, 412, 428, 429, 229, 230, 231, 235, 391, 465

[56] **References Cited**

U.S. PATENT DOCUMENTS

Re. 33,900	4/1992	Howson	370/105
4,437,087	3/1984	Petr	340/347 DD
4,438,511	3/1984	Baran	370/19
4,506,358	3/1985	Montgomery	370/60
4,646,287	2/1987	Larson et al.	370/60
4,677,423	6/1987	Benvenuto et al.	340/347
4,678,189	7/1987	Olson et al.	370/60
4,679,227	7/1987	Hughes-Hartogs	379/98
4,723,267	2/1988	Jones et al.	379/93
4,731,816	3/1988	Hughes-Hartogs	379/98
4,750,136	6/1988	Arpin et al.	364/514
4,757,495	7/1988	Decker et al.	370/76
4,769,810	9/1988	Eckberg, Jr. et al.	370/60
4,769,811	9/1988	Eckberg, Jr. et al.	370/60
4,827,411	5/1989	Arrowood et al.	364/300
4,833,706	5/1989	Hughes-Hartogs	379/98
4,835,737	5/1989	Herrig et al.	364/900

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

0 384 758	2/1990	European Pat. Off.	H04L 12/56
0 431 751 A1	11/1990	European Pat. Off.	H04I 12/46
WO 95/20850	8/1995	WIPO	H04L 12/56

OTHER PUBLICATIONS

Chowdhury, et al., "Alternative Banddwidth Allocation Algorithms for Packet Video in ATM Networks", 1992, IEEE Infocom 92, pp. 1061–1068.

Zhang, et al., "Rate–Controlled Static–Priority Queueing", 1993, IEEE, pp. 227–236.

Doeringer, et al., "Routing on Longest–Matching Prefixes", IEEE ACM Transactions on Networking, Feb. 1, 1996, vol. 4, No. 1, pp. 86–97.

IBM, "Method and Apparatus for the Statistical Multiplexing of Voice, Data, and Image Signals", Nov., 1992, IBM Technical Data Bulletin n6 11–92, pp. 409–411.

(List continued on next page.)

Primary Examiner—Chi H. Pham
Assistant Examiner—Ricky Q. Ngo
Attorney, Agent, or Firm—Swernofsky Law Group

[57] **ABSTRACT**

A pipelined multiple issue architecture for a link layer or protocol layer packet switch, which processes packets independently and asynchronously, but reorders them into their original order, thus preserving the original incoming packet order. Each stage of the pipeline waits for the immediately previous stage to complete, thus causing the packet switch to be self-throttling and thus allowing differing protocols and features to use the same architecture, even if possibly requiring differing processing times. The multiple issue pipeline is scaleable to greater parallel issue of packets, and tunable to differing switch engine architectures, differing interface speeds and widths, and differing clock rates and buffer sizes. The packet switch comprises a fetch stage, which fetches the packet header into one of a plurality of fetch caches, a switching stage comprising a plurality of switch engines, each of which independently and asychronously reads from corresponding fetch caches, makes switching decisions, and write to a reorder memory, a reorder engine which reads from the reorder memory in the packets' original order, and a post-processing stage, comprising a post-process queue and a post-process engine, which performs protocol-specific post-processing on the packets.

40 Claims, 5 Drawing Sheets



DUAL ISSUE SWITCH: PACKETS AND CONTROL FLOW

U.S. PATENT DOCUMENTS

4,922,486	5/1990	Lidinsky et al.	370/60
4,960,310	10/1990	Cushing	350/1.7
4,965,772	10/1990	Daniel et al.	364/900
4,979,118	12/1990	Kheradpir	364/436
4,980,897	12/1990	Decker et al.	375/38
5,014,265	5/1991	Hahne et al.	370/60
5,054,034	10/1991	Hughes-Hartogs	375/8
5,095,480	3/1992	Fenner	370/94.1
5,206,889	4/1993	Bingham	375/97
5,208,811	5/1993	Kashio et al. .	
5,228,062	7/1993	Bingham	375/97
5,247,516	9/1993	Bernstein et al.	370/82
5,253,251	10/1993	Aramaki	370/394
5,280,470	1/1994	Buhrke et al.	370/13
5,287,103	2/1994	Kasprzyk et al.	340/825.52
5,287,453	2/1994	Roberts	395/200
5,309,437	5/1994	Perlman et al.	730/85.13
5,327,421	7/1994	Hiller et al.	370/61.1
5,345,445	9/1994	Hiller et al.	370/60.1
5,345,446	9/1994	Hiller et al.	370/60.1
5,365,524	11/1994	Hiller et al.	370/94.2
5,367,517	11/1994	Cidon et al.	370/54
5,371,852	12/1994	Attanasio et al.	395/200
5,390,175	2/1995	Hiller et al.	370/60
5,414,705	5/1995	Therasse et al.	370/394
5,422,882	6/1995	Hiller et al.	370/60.1
5,426,636	6/1995	Hiller et al.	370/60.1
5,428,607	6/1995	Hiller et al.	370/60.1
5,430,729	7/1995	Rahnema .	
5,442,457	8/1995	Najafi	385/400
5,452,297	9/1995	Hiller et al.	370/60.1
5,477,541	12/1995	White et al. .	
5,483,523	1/1996	Nederlof	370/394
5,485,455	1/1996	Dobbins et al.	370/60
5,490,140	2/1996	Abensour et al. .	
5,490,258	2/1996	Fenner	395/401
5,497,371	3/1996	Ellis et al.	370/394
5,519,858	5/1996	Walton et al.	395/600
5,535,195	7/1996	Lee	370/54
5,539,734	7/1996	Burwell et al. .	
5,541,911	7/1996	Nilakantan et al. .	
5,546,370	8/1996	Ishikawa .	
5,548,593	8/1996	Peschi	370/394
5,555,244	9/1996	Gupta et al.	370/60
5,583,862	12/1996	Callon	370/397
5,590,122	12/1996	Sandorfi et al.	370/394
5,592,470	1/1997	Rudrapatna et al.	370/320
5,598,581	1/1997	Daines et al.	395/872
5,600,798	2/1997	Chenrukuri et al. .	
5,604,868	2/1997	Komine et al.	395/200
5,608,733	3/1997	Vallee et al.	370/394
5,617,417	4/1997	Sathe et al.	370/394
5,617,421	4/1997	Chin et al.	370/402
5,630,125	5/1997	Zellweger	395/614
5,631,908	5/1997	Saxe .	
5,632,021	5/1997	Jennings et al.	395/309
5,634,010	5/1997	Ciscon et al.	395/200
5,644,718	7/1997	Belove et al.	395/200
5,666,353	9/1997	Klausmeier et al.	370/230
5,673,265	9/1997	Gupta et al.	370/432
5,678,006	10/1997	Valizadeh et al.	395/200
5,680,116	10/1997	Hashimoto et al. .	
5,684,797	11/1997	Aznar et al.	370/390
5,687,324	11/1997	Green et al. .	
5,689,506	11/1997	Chiussi et al.	370/388
5,724,351	3/1998	Chao et al. .	
5,748,186	5/1998	Raman	345/302
5,754,547	5/1998	Nakazawa .	
5,802,054	9/1998	Bellenger .	
5,835,710	11/1998	Nagami et al. .	
5,854,903	12/1998	Morrison et al. .	
5,856,981	1/1999	Voelker .	
5,892,924	4/1999	Lyon et al.	395/200.75
5,898,686	4/1999	Virgile .	
5,903,559	5/1999	Acharya et al. .	

OTHER PUBLICATIONS

Esaki, et al., "Datagram Delivery in an ATM–Internet," IEICE Transactions on Communications vol. E77–B, No. 3, (1994) Mar. Tokyo, Japan.

William Stallings, Data and Computer Communications, pp. 329–333, Prentice Hall, Upper Saddle River, New Jersey 07458.


110
100
103
PACKET
104
PACKET
HEADER
PACKET
MEMORY
PACKET
SWITCH
101
101
NETWORK
INTERFACE
102
NETWORK
102

FIG. 1


100
SWITCHING STAGE
220
PROCESS ORDER NOW AT N-1
REORDER & REWRITE
N-2 (AVAIL.) RESULTS BUF. I
N-1 RESULTS BUF. II
N RESULTS BUF. III
N+1 RESULTS BUF. IV
223
222
SWITCH ENG. I
PROCESS N
PROCESS N+1
SWITCH ENG. II
221
MEM.
FETCH STAGE
210
fetch_on_demand
CACHE I
CACHE II
N
N+1
N+2
N+3
212
FETCH ENG.
211
PACKET HEADER FROM SYSTEM MEMORY
POST PROCESS STAGE
230
231
NEXT PACKET N-2
PROCESSED PACKET N-3
POST PROCESSOR
232
TO SYSTEM MEMORY
PIPELINE FLOW CONTROL
PIPELINE DATA FLOW
NOTE:
Result I – IV each are 16 byte result registers
SE I always toggles between result buf. I & III.
SE II always toggles between result buf. II & IV.
SWITCH ENGINE I – PROCESS EVEN PACKETS
SWITCH ENGINE II – PROCESS ODD PACKETS
DUAL ISSUE SWITCH: PACKETS AND CONTROL FLOW

FIG. 2A


100
FETCH STAGE
210
SWITCHING AND
REORDER/REWRITE
220
POST PROCESSING
230
FROM
PACKET
MEMORY
TO
PACKET
MEMORY
FETCH
ENG.
211
212
N
N+1
N+2
N+3
N+4
N+5
N+6
N+7
221
SWITCH
ENG. 1
SWITCH
ENG. 2
SWITCH
ENG. 3
SWITCH
ENG. 4
NOW AT
N-4
222
223
N
N+1
N+2
N+3
N-4
N-3
N-2
N-1
231
N-5
N-6
POST
PROCESSOR
232
POST PROCESSING UNIT
AN EXAMPLE OF A FOUR WAY L3 SWITCH (MAX 14 PACKETS IN THE PIPE)

FIG. 2B


FETCH ENGINE
211
SWITCH ENGINE
221
DATA NOT REQUIRED
307
DATA VALID
303
FROM
300
317
R
305
315
316
212
CACHE
0
CACHE
1
CACHE
2
CACHE
3
311
312
313
314
305
306
R
W
302
304
307
310
DATA
FETCH
STATE
MACHINE
300
PACKET
MEMORY
301
110

FIG. 3


410
400
411
MEMORY
100
411
110
PACKET SWITCH
MEMORY
412
PACKET MEMORY
411
REORDER PROCESSOR
PACKET SWITCH
MEMORY
411
100
MEMORY

FIG. 4

PIPELINED MULTIPLE ISSUE PACKET SWITCH

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to a pipelined multiple issue packet switch.

2. Description of Related Art

When computers are coupled together into networks for communication, it is known to couple networks together and to provide a switching device which is coupled to more than one network. The switching device receives packets from one network and retransmits those packets (possibly in another format) on another network. In general, it is desirable for the switching device to operate as quickly as possible.

However, there are several constraints under which the switching device must operate. First, packets may encapsulate differing protocols, and thus may differ significantly in length and in processing time. Second, when switching packets from one network to another, it is generally required that packets are re-transmitted in the same order as they arrive. Because of these two constraints, known switching device architectures are not able to take advantage of significant parallelism in switching packets.

It is also desirable to account ahead of time for future improvements in processing hardware, such as bandwidth and speed of a network interface, clock speed of a switching processor, and memory size of a packet buffer, so that the design of the switching device is flexible and scaleable with such improvements.

The following U.S. Patents may be pertinent:

U.S. Pat. No. 4,446,555 to Devault et al., "Time Division Multiplex Switching Network For Multiservice Digital Networks";

U.S. Pat. No. 5,212,686 to Joy et al., "Asynchronous Time Division Switching Arrangement and A Method of Operating Same";

U.S. Pat. No. 5,271,004 to Proctor et al., "Asynchronous Transfer Mode Switching Arrangement Providing Broadcast Transmission"; and

U.S. Pat. No. 5,307,343 to Bostica et al., "Basic Element for the Connection Network of A Fast Packet Switching Node".

Accordingly, it would be advantageous to provide an improved architecture for a packet switch, which can make packet switching decisions responsive to link layer (ISO level 2) or protocol layer (ISO level 3) header information, which is capable of high speed operation at relatively low cost, and which is flexible and scaleable with future improvements in processing hardware.

SUMMARY OF THE INVENTION

The invention provides a pipelined multiple issue link layer or protocol layer packet switch, which processes packets independently and asynchronously, but reorders them into their original order, thus preserving the original incoming packet order. Each stage of the pipeline waits for the immediately previous stage to complete, thus causing the packet switch to be self-throttling and thus allowing differing protocols and features to use the same architecture, even if possibly requiring differing processing times. The multiple issue pipeline is scaleable to greater parallel issue of packets, and tunable to differing switch engine architectures, differing interface speeds and widths, and differing clock rates and buffer sizes.

In a preferred embodiment, the packet switch comprises a fetch stage, which fetches the packet header into one of a plurality of fetch caches, a switching stage comprising a plurality of switch engines, each of which independently and asychronously reads from corresponding fetch caches, makes switching decisions, and writes to a reorder memory, a reorder engine which reads from the reorder memory in the packets' original order, and a post-processing stage, comprising a post-process queue and a post-process engine, which performs protocol-specific post-processing on the packets.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** shows the placement of a packet switch in an internetwork.

FIG. **2** shows a block diagram of a packet switch. FIG. **2** comprises FIG. **2**A and FIG. **2**B collectively.

FIG. **3** shows a fetch stage for the packet switch.

FIG. **4** shows a block diagram of a system having a plurality of packet switches in parallel.

DESCRIPTION OF THE PREFERRED EMBODIMENT

In the following description, a preferred embodiment of the invention is described with regard to preferred process steps, data structures, and switching techniques. However, those skilled in the art would recognize, after perusal of this application, that embodiments of the invention may be implemented using a set of general purpose computers operating under program control, and that modification of a set of general purpose computers to implement the process steps and data structures described herein would not require undue invention.

The present invention may be used in conjunction with technology disclosed in the following copending application.

Application Ser. No. 08/229,289, filed Apr. 18, 1994, in the name of inventors Bruce A. Wilford, Bruce Sherry, David Tsiang, and Anthony Li, titled "Packet Switching Engine" now U.S. Pat. No. 5,509,006.

This application is hereby incorporated by reference as if fully set forth herein, and is referred to herein as the "Packet Switching Engine disclosure".

PIPELINED, MULTIPLE ISSUE PACKET SWITCH

FIG. **1** shows the placement of a packet switch in an internetwork.

A packet switch **100** is coupled to a first network interface **101** coupled to a first network **102** and a second network interface **101** coupled to a second network **102**. When a packet **103** is recognized by the first network interface **101** (i.e., the MAC address of the packet **103** is addressed to the packet switch **100** or to an address known to be off the first network **102**), the packet **103** is stored in a packet memory **110** and a pointer to a packet header **104** for the packet **103** is generated.

In a preferred embodiment, the packet header **104** comprises a link layer (level **2**) header, and a protocol layer (level **3**) header. The link layer header, sometimes called a "MAC" (media access control) header, comprises information for communicating the packet **103** on a network **102** using particular media, such as the first network **102**. The protocol layer header comprises information for level **3**

switching of the packet **103** among networks **102**. The link layer header comprises information for level **2** switching (i.e., bridging). For example, the link layer header may comprise an ethernet, FDDI, or token ring header, while the protocol layer header may comprise an IP header. Also, there are hybrid switching techniques which respond to the both the level **2** and the level **3** headers, as well as those which respond to level **4** headers (such as extended access lists). Those skilled in the art will recognize, after perusal of this application, that other types of packet headers or trailers are within the scope and spirit of the invention, and that adapting the invention to switching such packet headers would not involve invention or undue experimentation.

The packet switch **100** reads the packet header **104** and performs two tasks—(1) it rewrites the packet header **104**, if necessary, to conform to protocol rules for switching the packet **103**, and (2) it queues the packet **103** for transmission on an output network interface **101** and thus an output network **102**. For example, if the output network **102** requires a new link layer header, the packet switch **100** rewrites the link layer header. If the protocol layer header comprises a count of the number of times the packet **103** has been switched, the packet switch **100** increments or decrements that count, as appropriate, in the protocol layer header.

FIG. **2** shows a block diagram of a packet switch. FIG. **2** comprises FIG. **2**A and FIG. **2**B collectively.

The packet switch **100** comprises a fetch stage **210**, a switching stage **220**, and a post-processing stage **230**.

The pointer to the packet header **104** is coupled to the fetch stage **210**. The fetch stage **210** comprises a fetch engine **211** and a plurality of (preferably two) fetch caches **212**. Each fetch cache **212** comprises a double buffered FIFO queue.

FIG. **2**A shows a preferred embodiment in which there are two fetch caches **212**, while FIG. **2**B shows an alternative preferred embodiment in which there are four fetch caches **212**.

In response to a signal from the switching stage **220**, the fetch engine **211** prefetches a block of M bytes of the packet header **104** and stores that block in a selected FIFO queue of a selected fetch cache **212**. In a preferred embodiment, the value of M, the size of the block, is independent of the protocol embodied in the protocol link layer, and is preferably about 64 bytes. In alternative embodiments, the value of M may be adjusted, e.g., by software, so that the packet switch **100** operates most efficiently with a selected mix of packets **103** it is expected to switch.

When the block of M bytes does not include the entire packet header **104**, the fetch engine **211** fetches, in response to a signal from the fetch cache **212**, a successive block of L additional bytes of the packet header **104** and stores those blocks in the selected FIFO queue of the selected fetch cache **212**, thus increasing the amount of data presented to the switching stage **220**. In a preferred embodiment, the value of L, the size of the additional blocks, is equal to the byte width of an interface to the packet memory **110**, and in a preferred embodiment is about 8 bytes.

After storing at least a portion of a packet header **104** in a fetch cache **212**, the fetch engine **211** reads the next packet header **104** and proceeds to read that packet header **104** and store it in a next selected fetch cache **212**. The fetch caches **212** are selected for storage in a round-robin manner. Thus when there are N fetch caches **212**, each particular fetch cache **212** receives every Nth packet header **104** for storage; when there are two fetch caches **212**, each particular fetch cache **212** receives every other packet header **104** for storage.

Each fetch cache **212** is double buffered, so that the fetch engine **211** may write a new packet header **104** to a fetch cache **212** while the corresponding switch engine **221** is reading from the fetch cache **212**. This is in addition to the fetch on demand operation described above, in which the fetch engine **211** writing successive blocks of additional bytes of an incomplete packet header **104** in response to a signal from a switch engine **221**. Thus each particular fetch cache **212** pipelines up to two packet headers **104**; when there are N fetch caches **212**, there are up to 2N packet headers **104** pipelined in the fetch stage **210**.

More generally, there may be N fetch caches **212**, each of which comprises B buffers, for a total of BN buffers. The fetch engine **211** writes new packet headers **104** in sequence to the N fetch caches **212** in order, and when the fetch engine **211** returns to a fetch cache **212** after writing in sequence to all other fetch caches **212**, it writes in sequence to the next one of the B buffers within that fetch cache **212**.

As shown below, the switching stage **220** comprises an identical number N of switch engines **221**, each of which reads in sequence from one of the B buffers of its designated fetch cache **212**, returning to read from a buffer after reading in sequence from all other buffers in that fetch cache **212**.

In FIG. **2**A, a preferred embodiment in which there are two fetch caches **212**, there are four packet headers **104** pipelined in the fetch stage **210**, labeled n+3, n+2, n+1, and n. In FIG. **2**B, an alternative preferred embodiment in which there are four fetch caches **212**, there are eight packet headers **104** pipelined in the fetch stage **210**, labeled n+7, n+6, n+5, n+4, n+3, n+2, n+1, and n.

The fetch stage **210** is further described with regard to FIG. **3**.

The switching stage **220** comprises a plurality of switch engines **221**, one for each fetch cache **212**, and a reorder/rewrite engine **222**.

Each switch engine **221** is coupled to a corresponding fetch cache **212**. Each switch engine **221** independently and asychronously reads from its corresponding fetch cache **212**, makes a switching decision, and writes its results to one of a plurality of (preferably two) reorder/rewrite memories **223** in the reorder/rewrite engine **222**. Thus, when there are N fetch caches **212**, there are also N switch engines **221**, and when there are K reorder/rewrite memories **223** for each switch engine **221**, there are KN reorder/rewrite memories **223** in N sets of K.

FIG. **2**A shows a preferred embodiment in which there are two switch engines **221** and four reorder/rewrite memories **223**, while FIG. **2**B shows an alternative preferred embodiment in which there are four switch engines **221** and eight reorder/rewrite memories **223**.

In a preferred embodiment, each switch engine **221** comprises a packet switch engine as shown in the Packet Switching Engine disclosure. The switching results and other data (e.g., statistical information) written into the reorder/rewrite memories **223** comprise information regarding how to rewrite the packet header **104** and to which network interface **101** to output the packet **103**. Preferably, this information comprises results registers as described in the Packet Switching Engine disclosure, and includes a pointer to the packet header **104** in the packet memory **110**.

Preferably, a single integrated circuit chip comprises significant circuits of at least one, and preferably more than one, switch engine **221**.

As described in the Packet Switching Engine disclosure, each switch engine **221** reads instructions from a "tree

memory" comprising instructions for reading and interpreting successive bytes of the packet header **104**. In a preferred embodiment, the tree memory comprises a set of memory registers coupled to the switch engine **221**. In an alternative embodiment, at least some of the tree memory may be cached on the integrated circuit chip for the switch engine **221**.

The reorder/rewrite engine **222** reads from the reorder/rewrite memories **223** in a preselected order. The N sets of K reorder/rewrite memories **223** are interleaved, so that results from the switch engines **221** are read in a round-robin manner. Thus, output from the reorder/rewrite engine **222** is in the original order in which packets **103** arrived at the packet switch **100**.

Thus, each one of the switch engines **221** writes in sequence to its K designated reorder/rewrite memories **223**, returning to one of its designated reorder/rewrite memories **223** after writing in sequence to its other designated reorder/rewrite memories **223**. In parallel, the reorder/rewrite engine **222** reads in sequence from all the NK reorder/rewrite memories **223**, and returns to one of the NK reorder/rewrite memories **223** after reading in sequence from all other reorder/rewrite memories **223**.

In FIG. **2**A, a preferred embodiment in which there are two switch engines **221** and four reorder/rewrite memories **223**, there are four packet headers **104** pipelined in the switching stage **220**, labeled n+1, n, n−1, and n−2 (now available). In FIG. **2**B, an alternative preferred embodiment in which there are four switch engines **221** and eight reorder/rewrite memories **223**, there are eight packet headers **104** pipelined in the switching stage **220**, labeled n+3, n+2, n+1, n, n−1, n−2, n−3, and n−4.

The reorder/rewrite engine **222**, in addition to receiving the packet headers **104** in their original order from the reorder/rewrite memories **223**, may also rewrite MAC headers for the packet headers **104** in the packet memory **110**, if such rewrite is called for by the switching protocol.

The post-processing stage **230** comprises a post-processing queue **231** and a post-processor **232**.

The reorder/rewrite engine **222** writes the packet headers **104** into a FIFO queue of post-processing memories **231** in the order it reads them from the reorder/rewrite memories **223**. Because the queue is a FIFO queue, packet headers **104** leave the post-processing stage **230** in the same order they enter, which is the original order in which packets **103** arrived at the packet switch **100**.

The post-processor **232** performs protocol-specific operations on the packet header **104**. For example, the post-processor **232** increments hop counts and recomputes header check-sums for IP packet headers **104**. The post-processor **232** then queues the packet **103** for the designated output network interface **101**, or, if the packet **103** cannot be switched, discards the packet **103** or queues it for processing by a route server, if one exists.

In FIG. **2**A, a preferred embodiment, and in FIG. **2**B, an alternative preferred embodiment, there are two post-processing memories **231** in the FIFO queue for the post-processing stage **230**. In FIG. **2**A there are two packet headers **104** pipelined in the post-processing stage **230**, labeled n−3 and n−2.In FIG. **2**B there are two packet headers **104** pipelined in the post-processing stage **230**, labeled n−6 and n−5.

FIG. **2**A, a preferred embodiment, and FIG. **2**B, an alternative preferred embodiment, show that there are several packet headers **104** processed in parallel by the packet switch **100**. In general, where there are S switching engines **211**, there are 3S+2 packet headers **104** processed in parallel by the packet switch **100**. Of these, 2S packet headers **104** are stored in the fetch stage **210**, S packet headers **104** are stored in the reorder/rewrite memories **223**, and 2 packet headers **104** are stored in the post-processing stage **230**.

In a preferred embodiment, the packet memory **110** is clocked at about 50 MHz and has a memory fetch path to the fetch stage **210** which is eight bytes wide, there are two switching engines **221**, each of which operates at an average switching speed of about 250 kilopackets switched per second, and each stage of the packet switch **100** completes operation within about 2 microseconds. Although each switching engine **221** is individually only about half as fast as the pipeline processing speed, the accumulated effect when using a plurality of switching engines **221** is to add their effect, producing an average switching speed for the packet switch **100** of about 500 kilopackets switched per second when the pipeline is balanced.

In an alternative preferred embodiment, each switching engine **221** operates at an average switching speed of about 125 kilopackets switched per second, producing an average switching speed for the packet switch **100** of about 250 kilopackets switched per second when the pipeline is balanced. Because the pipeline is limited by its slowest stage, the overall speed of the packet switch **100** is tunable by adjustment of parameters for its architecture, including speed of the memory, width of the memory fetch path, size of the cache buffers, and other variables. Such tunability allows the packet switch **100** to achieve satisfactory performance at a reduced cost.

FETCH ENGINE AND FETCH MEMORIES

FIG. **3** shows a fetch stage for the packet switch.

The fetch engine **211** comprises a state machine **300** having signal inputs coupled to the packet memory **110** and to the switching stage **220**, and having signal outputs coupled to the switching stage **220**.

A packet ready signal **301** is coupled to the fetch engine **211** from the packet memory **110** and indicates whether there is a packet header **104** ready to be fetched. In this description of the fetch engine **211**, it is presumed that packets **103** arrive quickly enough that the packet ready signal **301** indicates that there is a packet header **104** ready to be fetched at substantially all times. If the fetch engine **211** fetches packet headers **104** quicker than those packet headers **104** arrive, at some times the fetch engine **211** (and the downstream elements of the packet switch **100**) will have to wait for more packets **103** to switch.

A switch ready signal **302** is coupled to the fetch engine **211** from each of the switch engines **221** and indicates whether the switch engine **211** is ready to receive a new packet header **104** for switching.

A data available (or cache ready) signal **303** is coupled to each of the switch engines **221** from the fetch engine **211** and indicates whether a packet header **104** is present in the fetch cache **212** for switching.

A cache empty signal **304** is coupled to the fetch engine **211** from each of the fetch caches **212** and indicates whether the corresponding switch engine **211** has read all the data from the packet header **104** supplied by the fetch engine **211**. A data not required signal **307** is coupled to the fetch engine **211** from each of the switch engines **211** and indicates whether the switch engine **211** needs further data loaded into the fetch cache **212**.

It may occur that the switch engine **211** is able to make its switching decision without need for further data from the

packet header **104**, even though the switch engine **211** has read all the data from the packet header **104** supplied by the fetch engine **211**. In this event, the switch engine **211** sets the data not required signal **307** to inform the fetch engine **211** that no further data should be supplied, even though the cache empty signal **304** has been triggered.

It may also occur that the switch engine **211** is able to determine that it can make its switching decision within the data already available, even if it has not made that switching decision yet. For example, in the IP protocol, it is generally possible to make the switching decision with reference only to the first 64 bytes of the packet header **104**. If the switch engine **211** is able to determine that a packet header **104** is an IP packet header, it can set the data not required signal **307**.

A read pointer **305** is coupled to each of the fetch caches **212** from the corresponding switch engine **221** and indicates a location in the fetch cache **212** where the switch engine **221** is about to read a word (of a packet header **104**) from the fetch cache **212**.

A write pointer **306** is coupled to each of the fetch caches **212** from the fetch engine **211** and indicates a location in the fetch cache **212** where the fetch engine **211** is about to write a word (of a packet header **104**) to the fetch cache **212**.

A first pair of fetch caches **212** (labeled "0" and "1") and a second pair of fetch caches **212** (labeled "2" and "3")each comprise dual port random access memory (RAM), preferably a pair of 16 word long by 32 bit wide dual port RAM circuits disposed to respond to addresses as a single 16 word long by 64 bit wide dual port RAM circuit.

A 64 bit wide data bus **310** is coupled to a data input for each of the fetch caches **212**.

The read pointers **305** for the first pair of the fetch caches **212** (labeled as "0" and "1") are coupled to a first read address bus **311** for the fetch caches **212** using a first read address multiplexer **312**. The two read pointers **305** are data inputs to the read address multiplexer **312**; a select input to the read address multiplexer **312** is coupled to an output of the fetch engine **211**. Similarly, the read pointers **305** for the second pair of the fetch caches **212** (labeled as "2" and "3") are coupled to a second read address bus **311** for the fetch caches **212** using a second read address multiplexer **312**, and selected by an output of the fetch engine **211**.

Similarly, the write pointers **306** for the first pair of the fetch caches **212** (labeled as "0" and "1") are coupled to a first write address bus **313** for the fetch caches **212** using a first write address multiplexer **314**. The two write pointers **306** are data inputs to the write address multiplexer **314**; a select input to the write address multiplexer **314** is coupled to an output of the fetch engine **211**. Similarly, the write pointers **306** for the second pair of the fetch caches **212** (labeled as "2" and "3")are coupled to a second write address bus **313** for the fetch caches **212** using a second write address multiplexer **314**, and selected by an output of the fetch engine **211**.

An output **315** for the first pair of fetch caches **212** is coupled to a byte multiplexer **316**. The byte multiplexer **316** selects one of eight bytes of output data, and is selected by an output of a byte select multiplexer **317**. The byte select multiplexer **317** is coupled to a byte address (the three least significant bits of the read pointer **305**) for each of the first pair of fetch caches **212**, and is selected by an output of the fetch engine **211**.

An initial value for the byte address (the three least significant bits of the read pointer **305**) may be set by the state machine **300** to allow a first byte of the packet header **104** to be offset from (i.e., not aligned with) an eight-byte block in the packet memory **110**. The state machine **300** resets the byte address to zero for successive sets of eight bytes to be fetched from the packet memory **110**.

Similarly, an output **315** for the second pair of fetch caches **212** is coupled to a byte multiplexer **316**. The byte multiplexer **316** selects one of eight bytes of output data, and is selected by an output of a byte select multiplexer **317**. The byte select multiplexer **317** is coupled to a byte address (the three least significant bits of the read pointer **305**) for each of the second pair of fetch caches **212**, and is selected by an output of the fetch engine **211**. The byte multiplexers **316** are coupled to the switching stage **220**.

As described with regard to FIG. **2**, the fetch engine **211** responds to the switch ready signal **302** from a switch engine **221** by prefetching the first M bytes of the packet header **104** from the packet memory **110** into the corresponding fetch cache **212**. To perform this task, the fetch engine **211** selects the write pointer **306** for the corresponding fetch cache **212** using the corresponding write address multiplexer **314**, writes M bytes into the corresponding fetch cache **212**, and updates the write pointer **306**.

As described with regard to FIG. **2**, the fetch cache **212** raises the cache empty signal **304** when the read pointer **305** approaches the write pointer **306**, such as when the read pointer **305** is within eight bytes of the write pointer **306**. The fetch engine **211** responds to the cache empty signal **304** by fetching the next L bytes of the packet header **104** from the packet memory **110** into the corresponding fetch cache **212**, unless disabled by the data not required signal **307** from the switch engine **221**. To perform this task, the fetch engine **211** proceeds in like manner as when it prefetched the first M bytes of the packet header **104**.

In a preferred embodiment, the fetch cache **212** includes a "watermark" register (not shown) which records an address value which indicates, when the read pointer **305** reaches that address value, that more data should be fetched. For example, the watermark register may record a value just eight bytes before the write pointer **306**, so that more data will only be fetched when the switch engine **221** is actually out of data, or the watermark register may record a value more bytes before the write pointer **306**, so that more data will be fetched ahead of actual need. Too-early values may result in data being fetched ahead of time without need, while too-late values may result in the switch engine **221** having to wait. Accordingly, the value recorded in the watermark register can be adjusted to better match the rate at which data is fetched to the rate at which data is used by the switch engine **221**.

While the switch engine **221** reads from the fetch cache **212**, the fetch engine **211** prefetches the first M bytes of another packet header **104** from the packet memory **110** into another fetch cache **212** (which may eventually comprise the other fetch cache **212** of the pair). To perform this task, the fetch engine **211** selects the write pointer **306** for the recipient fetch cache **212** using the corresponding write address multiplexer **314**, writes M bytes into the recipient fetch cache **212**, and updates the corresponding write pointer **306**.

The switch engines **221** are each coupled to the read pointer **305** for their corresponding fetch cache **212**. Each switch engine **221** independently and asychronously reads from its corresponding fetch cache **212** and processes the packet header **104** therein. To perform this task, the switch engine **221** reads one byte at a time from the output of the output multiplexer **320** and updates the corresponding byte

address (the three least significant bits of the read pointer **305**). When the read pointer **305** approaches the write pointer **306**, the cache low signal **304** is raised and the fetch engine **211** fetches L additional bytes "on demand".

MULTIPLE PACKET SWITCHES IN PARALLEL

FIG. **4** shows a block diagram of a system having a plurality of packet switches in parallel.

In a parallel system **400**, the packet memory **110** is coupled in parallel to a plurality of (preferably two) packet switches **100**, each constructed substantially as described with regard to FIG. **1**. Each packet switch **100** takes its input from the packet memory **110**. However, the output of each packet switch **100** is directed instead to a reorder stage **410**, and an output of the reorder stage **410** is directed to the packet memory **110** for output to a network interface **101**.

The output of each packet switch **100** is coupled in parallel to the reorder stage **410**. The reorder stage **410** comprises a plurality of reorder memories **411**, preferably two per packet switch **100** for a total of four reorder memories **411**. The reorder stage **410** operates similarly to the reorder/rewrite memories **222** of the packet switch **100**; the packet switches **100** write their results to the reorder memories **411**, whereinafter a reorder processor **412** reads their results from the reorder memories **411** and writes them in the original arrival order of the packets **103** to the packet memory **110** for output to a network interface **101**.

In a preferred embodiment where each packet switch **100** operates quickly enough to achieve an average switching speed of about 500 kilopackets per second and the reorder stage **410** operates quickly enough so that the pipeline is still balanced, the parallel system **400** produces a throughput of about 1,000 kilopackets switched per second.

Alternative embodiments of the parallel system **400** may comprise larger numbers of packet switches **100** and reorder/rewrite memories **411**. For example, in one alternative embodiment, there are four packet switches **100** and eight reorder/rewrite memories **411**, and the reorder stage **410** is greatly speeded up. In this alternative embodiment, the parallel system **400** produces a throughput of about 2,000 kilopackets switched per second.

Alternative Embodiments

Although preferred embodiments are disclosed herein, many variations are possible which remain within the concept, scope, and spirit of the invention, and these variations would become clear to those skilled in the art after perusal of this application.

We claim:

1. A packet switch comprising

a fetch engine coupled to a source of packet headers;

a plurality of fetch caches coupled to said fetch engine, and disposed to store at least portions of packet headers received therefrom;

a plurality of switch engines, each coupled to a corresponding one of said fetch caches, and disposed to read said portions of packet headers therefrom;

a plurality of reorder/rewrite buffers, each said reorder/rewrite buffer coupled to one of said switch engines, and disposed to store pointers to packet headers received from at least one of said plurality of switch engines;

a reorder/rewrite engine coupled to said plurality of reorder/rewrite buffers, and disposed to read pointers to packet headers therefrom in an order said packet headers were originally received;

a post-process queue coupled to said reorder/rewrite engine, and disposed to store pointers to packet headers received therefrom; and

a post-process engine coupled to said post-process queue, and disposed to process said packet headers.

2. A packet switch comprising:

a switching stage;

a fetch stage coupled to a source of packet headers, said fetch stage being disposed to fetch at least portions of packet headers and present said portions of packet headers in parallel to said switching stage;

said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post process stage; and

said post-process stage coupled to said switching stage, and being disposed to perform protocol-specific processing on said packet headers.

3. A packet switch as in claim **2**, wherein said switching stage comprises a plurality of switch engines, each being disposed to receive a packet header and to produce a set of results for switching said packet header such that the input order of said packet header is preserved.

4. A packet switch, comprising

a fetch stage coupled to a source of packet headers, said fetch stage being disposed to fetch at least portions of packet headers and present said portions of packet headers in parallel to a switching stage, wherein said fetch stage comprises a fetch engine, said fetch engine being disposed to fetch a first block of M bytes of a packet header in response to a first signal, and being disposed to fetch an additional block of L bytes of said packet header in response to a second signal;

said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage; and

said post-process stage coupled to said switching stage, and being disposed to perform protocol-specific processing on said packet headers.

5. A packet switch as in claim **4**, wherein said first signal indicates an empty fetch cache and wherein said second signal indicates a fetch cache with fewer than a selected number of unread bytes.

6. A packet switch as in claim **4**, wherein M is independent of said packet header.

7. A packet switch as in claim **4**, wherein M is adjusted according to said packet header.

8. A packet switch as in claim **4**, wherein L is equal to a byte width of an interface to said source of packet headers.

9. A packet switch, comprising

a fetch stage coupled to a source of packet headers, said fetch stage being disposed to fetch at least portions of packet headers and present said portions of packet headers in parallel to a switching stage, wherein said fetch stage comprises a plurality of fetch caches, each one of said fetch caches being coupled to said source of packet headers and each being disposed to store at least a portion of a packet header;

said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage; and

said post-process stage coupled to said switching stage, and being disposed to perform protocol-specific processing on said packet headers.

10. A packet switch as in claim **9**, wherein said switching stage comprises a plurality of switch engines, each being coupled to one said fetch cache and each being disposed to receive said portion of a packet header and to produce a set of results for switching said packet header.

11. A packet switch, comprising

a fetch stage coupled to a source of packet headers, said fetch stage being disposed to fetch at least portions of packet headers and present said portions of packet headers in parallel to a switching stage, wherein said fetch stage comprises a fetch engine coupled to said source of packet headers;

a plurality of fetch caches coupled to said fetch engine, each said fetch cache comprising a plurality of buffers;

wherein said fetch engine is disposed to write at least a portion of each said packet header in sequence to each said fetch cache in a selected buffer thereof;

wherein said switching stage comprises a switch engine for each said fetch cache, wherein each said switch engine is disposed to read at least a portion of said packet header in sequence from each said buffer of said fetch cache;

said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage; and

said post-process stage coupled to said switching stage, and being disposed to perform protocol-specific processing on said packet headers.

12. A packet switch as in claim **11**, wherein each said fetch cache is selected for storage in a round-robin manner.

13. A packet switch, comprising

a fetch stage coupled to a source of packet headers, said fetch stage being disposed to fetch at least portions of packet headers and present said portions of packet headers in parallel to a switching stage, wherein said switching stage comprises a plurality of reorder/rewrite memories, each one of said reorder/rewrite memories being disposed to store a pointer to a packet header;

said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage; and

said post-process stage coupled to said switching stage, and being disposed to perform protocol-specific processing on said packet headers.

14. A packet switch, comprising

a fetch stage coupled to a source of packet headers, said fetch stage being disposed to fetch at least portions of packet headers and present said portions of packet headers in parallel to a switching stage;

said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage;

said post-process stage coupled to said switching stage, and being disposed to perform protocol-specific processing on said packet headers; and

wherein said switching stage comprises

a plurality of switch engines, each being disposed to receive a packet header and to produce a set of results for switching said packet header;

a plurality of reorder/rewrite memories, each one of said reorder/ rewrite memories being disposed to store a packet header; and

a reorder/ rewrite processor coupled to said plurality of reorder/ rewrite memories and disposed to receive said packet headers from said reorder/ rewrite memories in an order in which said packet headers were originally received.

15. A packet switch, comprising

a fetch stage coupled to a source of packet headers, said fetch stage being disposed to fetch at least portions of packet headers and present said portions of packet headers in parallel to a switching stage;

said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage;

said post-process stage coupled to said switching stage, and being disposed to perform protocol-specific processing on said packet headers; and

wherein said switching stage comprises

a plurality of switch engines, each being disposed to receive a packet header and to produce a set of results for switching said packet header; and

a plurality of reorder/rewrite memories, each one of said reorder/rewrite memories being disposed to store a packet header;

said reorder/rewrite memories being divided into sets, each said set of reorder/rewrite memories being assigned to and receiving outputs from exactly one said switch engine.

16. A packet switch, comprising

a fetch stage coupled to a source of packet headers, said fetch stage being disposed to fetch at least portions of packet headers and present said portions of packet headers in parallel to a switching stage;

said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage;

said post-process stage coupled to said switching stage, and being disposed to perform protocol-specific processing on said packet headers; and

wherein said switching stage comprises

a plurality of switching engines, each said switching engine having a plurality of reorder/rewrite memories coupled thereto, each said switching engine being disposed to write in sequence to one of said plurality of reorder/rewrite memories; and

a reorder/rewrite engine coupled to all said reorder/ rewrite memories, said reorder/rewrite engine being disposed to read in sequence from said reorder/ rewrite memories.

17. A packet switch as in claim **16**, wherein said reorder/ rewrite engine is disposed to alter at least portions of packet headers referenced by said reorder/rewrite memories.

18. A packet switch, comprising

a fetch stage coupled to a source of packet headers, said fetch stage being disposed to fetch at least portions of packet headers and present said portions of packet headers in parallel to a switching stage;

said switching stage coupled to said fetch stage, said switching stare being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage;

said post-process stage coupled to said switching stage, and being disposed to perform protocol-specific processing on said packet headers, wherein said post-process stage comprises a plurality of post-processing memories, each one of said post-processing memories being disposed to store a pointer to a packet header.

19. A packet switch, comprising

a fetch stage coupled to a source of packet headers, said fetch stage being disposed to fetch at least portions of packet headers and present said portions of packet headers in parallel to a switching stage;

said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage;

said post-process stage coupled to said switching stage, and being disposed to perform protocol-specific processing on said packet headers, wherein said post-process stage comprises a post-processor coupled to said switching stage and disposed to alter at least a portion of a packet header responsive to a switching protocol.

20. A system, comprising

a packet memory;

a plurality of packet switches coupled to said packet memory;

a plurality of reorder memories coupled to said plurality of packet switches; and

a reorder engine coupled to said plurality of reorder memories and disposed to receive packet headers from said reorder memories in an order in which they were originally received;

wherein, each packet switch comprises a fetch stage coupled to said packet memory, said fetch state being disposed to fetch packet headers from said packet memory and present at least portions of packet headers in parallel to a switching stage; and said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage.

21. A system as in claim 20, wherein said switching stage comprises a plurality of switch engines, each being disposed to receive a packet header and to produce a set of results such that the in-out order of said packet header is preserved.

22. A system, comprising

a packet memory;

a plurality of reorder memories;

a reorder engine coupled to said plurality of reorder memories and disposed to receive packet headers from said reorder memories in an order in which they were originally received; and

a plurality of packet switches coupled to said packet memory and said plurality of reorder memories, wherein each one of said plurality of packet switches comprises

a fetch stage coupled to said packet memory, said fetch stage being disposed to fetch packet headers from said packet memory and present at least portions of packet headers in parallel to a switching stage, wherein said fetch stage comprises a fetch engine, said fetch engine being disposed to fetch a first block of M bytes of a packet header in response to a first signal, and being disposed to fetch an additional block of L bytes of said packet header in response to a second signal; and

said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage.

23. A system as in claim 22, wherein said first signal indicates an empty fetch cache and wherein said second signal indicates a fetch cache with fewer than a selected number of unread bytes.

24. A system, comprising

a packet memory;

a plurality of reorder memories;

a reorder engine coupled to said plurality of reorder memories and disposed to receive packet headers from said reorder memories in an order in which they were originally received; and

a plurality of packet switches coupled to said packet memory and said plurality of reorder memories, wherein each one of said plurality of packet switches comprises

a fetch stage coupled to said packet memory said fetch stage being disposed to fetch packet headers from said packet memory and present at least portions of packet headers in parallel to a switching stage, wherein said fetch stage comprises a plurality of fetch caches, each one of said fetch caches being coupled to said source of packet headers and each being disposed to store at least a portion of a packet header; and

said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage.

25. A system as in claim 24, wherein said switching stage comprises a plurality of switch engines, each being coupled to one said fetch cache and each being disposed to receive a packet header and to produce a set of results for switching said packet header.

26. A system, comprising

a packet memory;

a plurality of reorder memories;

a reorder engine coupled to said plurality of reorder memories and disposed to receive packet headers from said reorder memories in an order in which they were originally received; and

a plurality of packet switches coupled to said packet memory and said plurality of reorder memories, wherein each one of said plurality of packet switches comprises

a fetch stage coupled to said packet memory said fetch stage being disposed to fetch packet headers from said packet memory and present at least portions of packet headers in parallel to a switching stage, wherein said fetch stage comprises

a fetch engine coupled to said source of packet headers; and

a plurality of fetch caches coupled to said fetch engine, each said fetch cache comprising a plurality of buffers;

wherein said fetch engine is disposed to write at least a portion of each said packet header in sequence from each said fetch cache in a selected buffer thereof;

wherein said switching stage comprises a switch engine for each said fetch cache, wherein each said switch engine is disposed to read at least a portion of said packet header in sequence from each said buffer of said fetch cache;

said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage.

27. A system, comprising

a packet memory;

a plurality of reorder memories;

a reorder engine coupled to said plurality of reorder memories and disposed to receive packet headers from said reorder memories in an order in which they were originally received; and

a plurality of packet switches coupled to said packet memory and said plurality of reorder memories, wherein each one of said plurality of packet switches comprises

a fetch stage coupled to said packet memory said fetch stage being disposed to fetch packet headers from said packet memory and present at least portions of packet headers in parallel to a switching stage;

wherein said switching stage comprises

a plurality of switch engines, each being disposed to receive a packet header and to produce a set of results for switching said packet header;

a plurality of reorder/rewrite memories, each one of said reorder/rewrite memories being disposed to store a packet header; and

a reorder/rewrite processor coupled to said plurality of reorder/rewrite memories and disposed to receive said packet headers from said reorder/rewrite memories in an order in which said packet headers were originally received;

said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage.

28. A system as in claim **27**, wherein said reorder/rewrite processor is disposed to alter at least portions of said packet headers referenced by said reorder/rewrite memories.

29. A system, comprising

a packet memory;

a plurality of reorder memories;

a reorder engine coupled to said plurality of reorder memories and disposed to receive packet headers from said reorder memories in an order in which they were originally received; and

a plurality of packet switches coupled to said packet memory and said plurality of reorder memories, wherein each one of said plurality of packet switches comprises

a fetch stage coupled to said packet memory, said fetch stage being disposed to fetch packet headers from said packet memory and present at least portions of packet headers in parallel to a switching stage;

wherein said switching stage comprises

a plurality of switch engines, each being disposed to receive a packet header and to produce a set of results for switching said packet header; and

a plurality of reorder/rewrite memories, each one of said reorder/rewrite memories being disposed to store a packet header;

said reorder/rewrite memories being divided into sets, each said set of reorder/rewrite memories being assigned to and receiving outputs from exactly one said switch engine; and

said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage.

30. A system, comprising

a packet memory;

a plurality of reorder memories;

a reorder engine coupled to said plurality of reorder memories and disposed to receive packet headers from said reorder memories in an order in which they were originally received; and

a plurality of packet switches coupled to said packet memory and said plurality of reorder memories wherein each one of said plurality of packet switches comprises

a fetch stage coupled to said packet memory said fetch stage being disposed to fetch packet headers from said packet memory and present at least portions of packet headers in parallel to a switching stage;

wherein said switching stage comprises

a plurality of switching engines, each said switching engine having a plurality of reorder/rewrite memories coupled thereto, each said switching engine being disposed to write in sequence to one of said plurality of reorder/rewrite memories; and

a reorder/rewrite engine coupled to all said reorder/rewrite memories, said reorder/rewrite engine being disposed to read in sequence from said reorder/rewrite memories;

said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage.

31. A system, comprising

a packet memory;

a plurality of reorder memories;

a reorder engine coupled to said plurality of reorder memories and disposed to receive packet headers from said reorder memories in an order in which they were originally received; and

a plurality of packet switches coupled to said packet memory and said plurality of reorder memories, wherein each one of said plurality of packet switches comprises

a fetch stage coupled to said packet memory, said fetch stage being disposed to fetch packet headers from said packet memory and present at least portions of packet headers in parallel to a switching stage;

said switching stage coupled to said fetch stage, said switching stage being disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order to a post-process stage, wherein said switching stage comprises a plurality of reorder/rewrite memories, each one of said reorder/rewrite memories being disposed to store a pointer to a packet header.

32. A method of switching packets, said method comprising

fetching a sequence of packet headers corresponding to said packets from a source of said packet headers;

presenting said packet headers in parallel to a plurality of switch engines;

operating said switch engines to switch said packets asynchronously in parallel;

presenting switched packet headers in their original order to a post-processor; and

operating said post-processor to perform protocol-specific processing on said packet headers.

33. A method of switching packets, said method comprising

fetching a sequence of packet headers corresponding to said packets from a source of said packet headers, wherein said step of fetching includes fetching a first block of M bytes of a packet header in response to a first signal and fetching an additional block of L bytes of said packet header in response to a second signal;

presenting said packet headers in parallel to a plurality of switch engines;

operating said switch engines to switch said packets asynchronously in parallel;

presenting switched packet headers in their original order to a post-processor; and

operating said post-processor to perform protocol-specific processing on said packet headers.

34. A method as in claim 33, wherein said first signal indicates an empty fetch cache and wherein said second signal indicates a fetch cache with fewer than a selected number of unread bytes.

35. A method of switching packets, said method comprising

fetching a sequence of packet headers corresponding to said packets from a source of said packet headers, wherein said step of fetching includes storing said packet headers in sequence into a plurality of fetch caches;

presenting said packet headers in parallel to a plurality of switch engines;

operating said switch engines to switch said packets asynchronously in parallel;

presenting switched packet headers in their original order to a post-processor; and

operating said post-processor to perform protocol-specific processing on said packet headers.

36. A method of switching packets, said method comprising

fetching a sequence of packet headers corresponding to said packets from a source of said packet headers;

presenting said packet headers in parallel to a plurality of switch engines,

operating said switch engines to switch said packets asynchronously in parallel;

presenting switched packet headers in their original order to a post-processor; and

operating said post-processor to perform protocol-specific processing on said packet headers wherein said step of operating said post-processor stage comprises altering at least a portion of a packet header.

37. A method of switching packets, said method comprising

fetching a sequence of packet headers corresponding to said packets from a source of said packet headers;

presenting said packet headers in parallel to a plurality of switch engines;

operating said switch engines to switch said packets asynchronously in parallel, wherein said step of operating said switch engines includes coupling each said packet header to a selected fetch cache, coupling each said fetch cache to a selected switch engine, and coupling a set of results from said selected switch engine to a reorder/rewrite memory;

presenting switched packet headers in their original order to a post-processor; and

operating said post-processor to perform protocol-specific processing on said packet headers.

38. A method as in claim 37, wherein said reorder/rewrite memories are divided into sets, each said set of reorder/rewrite memories being assigned to and receiving outputs from exactly one said switch engine.

39. A system, including;

a packet memory;

a plurality of packet switches coupled to said packet memory, wherein each packet switch includes a fetch stage and a switching stage;

said fetch stage being coupled to said packet memory and disposed to fetch packet headers from said packet memory and present at least portions of said packet headers in parallel to said switching stage;

said switching stage being coupled to said fetch stage and disposed to switch said packet headers asynchronously in parallel and present said packet headers in their original order;

a plurality of reorder memories coupled to said plurality of packet switches; and

a reorder engine coupled to said plurality of reorder memories and disposed to receive packet headers from said reorder memories in an order in which they were originally received.

40. A system as in claim 39, wherein said switching stage comprises of a plurality of switch engines, each being disposed to receive a packet header and to produce a set of results such that the input order of said packet header is mimicked.

* * * * *